

FORM PTO-1590 (Mod/Rev) (REV 11-2000)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER 217867US2XPCT	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 10/030684)	
INTERNATIONAL APPLICATION NO. PCT/EP00/05941		INTERNATIONAL FILING DATE 20 JUNE 2000		PRIORITY DATE CLAIMED 14 JULY 1999	
TITLE OF INVENTION ACTUATION AND CONTROL DEVICE FOR ELECTRIC SWITCHGEAR					
APPLICANT(S) FOR DO/EO/US Enrico ELLI, et al.					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
<ol style="list-style-type: none"> 1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (24) indicated below. 4. <input checked="" type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (Article 31). 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371 (c) (2)) <ol style="list-style-type: none"> a. <input type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau). b. <input checked="" type="checkbox"/> has been communicated by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 6. <input type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)). <ol style="list-style-type: none"> a. <input type="checkbox"/> is attached hereto. b. <input type="checkbox"/> has been previously submitted under 35 U.S.C. 154(d)(4). 7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)) <ol style="list-style-type: none"> a. <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau). b. <input type="checkbox"/> have been communicated by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input checked="" type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)). 10. <input type="checkbox"/> An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)). 11. <input checked="" type="checkbox"/> A copy of the International Preliminary Examination Report (PCT/IPEA/409). 12. <input checked="" type="checkbox"/> A copy of the International Search Report (PCT/ISA/210). 					
Items 13 to 20 below concern document(s) or information included:					
<ol style="list-style-type: none"> 13. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 14. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 15. <input checked="" type="checkbox"/> A FIRST preliminary amendment. 16. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. 17. <input type="checkbox"/> A substitute specification. 18. <input type="checkbox"/> A change of power of attorney and/or address letter. 19. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825. 20. <input type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4). 21. <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4). 22. <input type="checkbox"/> Certificate of Mailing by Express Mail 23. <input checked="" type="checkbox"/> Other items or information: Notice of Priority / PCT/IB/304 / PCT/IB/308 PTO-1449 					


U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.101) 10/030684		INTERNATIONAL APPLICATION NO. PCT/EP00/05941		ATTORNEY'S DOCKET NUMBER 217867US2XPCT	
--	--	--	--	--	--

24. The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) : <input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$1040.00 <input checked="" type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$890.00 <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$740.00 <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$710.00 <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00				CALCULATIONS PTO USE ONLY	
ENTER APPROPRIATE BASIC FEE AMOUNT =				\$890.00	
Surcharge of \$130.00 for furnishing the oath or declaration later than months from the earliest claimed priority date (37 CFR 1.492 (e)). <input type="checkbox"/> 20 <input checked="" type="checkbox"/> 30				\$130.00	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	11 - 20 =	0	x \$18.00	\$0.00	
Independent claims	1 - 3 =	0	x \$84.00	\$0.00	
Multiple Dependent Claims (check if applicable).				<input type="checkbox"/> \$0.00	
TOTAL OF ABOVE CALCULATIONS =				\$1,020.00	
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				\$0.00	
SUBTOTAL =				\$1,020.00	
Processing fee of \$130.00 for furnishing the English translation later than months from the earliest claimed priority date (37 CFR 1.492 (f)). <input type="checkbox"/> 20 <input type="checkbox"/> 30 +				\$0.00	
TOTAL NATIONAL FEE =				\$1,020.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable).				<input type="checkbox"/> \$0.00	
TOTAL FEES ENCLOSED =				\$1,020.00	
				Amount to be:	
				refunded	\$
				charged	\$

a.	<input checked="" type="checkbox"/>	A check in the amount of <u>\$1,020.00</u> to cover the above fees is enclosed.
b.	<input type="checkbox"/>	Please charge my Deposit Account No. _____ in the amount of _____ to cover the above fees. A duplicate copy of this sheet is enclosed.
c.	<input checked="" type="checkbox"/>	The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>15-0030</u> A duplicate copy of this sheet is enclosed.
d.	<input type="checkbox"/>	Fees are to be charged to a credit card. WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:



22850

Surinder Sachar
Registration No. 34,423

(703) 413-3000

SIGNATURE _____

Marvin J. Spivak

NAME _____

24,913

REGISTRATION NUMBER _____

DATE Jan 14 2002

10030684 107030684

1070 Rec'd PCT/PTO 14 JAN 2002

217867US-2X PCT

IN THE UNITED STATES PATENT & TRADEMARK OFFICE

IN RE APPLICATION OF :
ENRICO ELLI ET AL : ATTN: APPLICATION DIVISION
SERIAL NO: NEW U.S. PCT APPLN :
(Based On PCT/EP00/005941)
FILED: HEREWITH :
FOR: ACTUATION AND CONTROL :
DEVICE FOR ELECTRIC
SWITCHGEAR

PRELIMINARY AMENDMENT

ASSISTANT COMMISSIONER FOR PATENTS
WASHINGTON, D.C. 20231

SIR:

Prior to a first examination on the merits, please amend the above-identified application as follows:

IN THE CLAIMS

Please amend the claims as follows:

3. (Amended) An actuation and control device according to claim 1, characterized in that position control is performed by a position sensor on the motor.

4. (Amended) An actuation and control device according to claim 1, characterized in that said motor with position control is a rotary servomotor.

5. (Amended) An actuation and control device according to claim 1, characterized by the fact that said electronic control and power supply unit comprises:

- calculating means suitable for predicting the zeros and maximums of the voltage and of the current of the phases subsequent to those detected by said measuring means and for calculating the period of time between the zeros and maximums detected and those predicted.

8. (Amended) A pole of a high-voltage circuit breaker, characterized in that it comprises an actuation and control device according to claim 1.

9. (Amended) A three-pole high-voltage circuit breaker for opening and closing a circuit connected thereto, characterized in that it comprises, for each pole, an actuation and control device according to claim 1.

10. (Amended) A three-pole high-voltage circuit breaker for opening and closing a circuit connected thereto, characterized in that it comprises an actuation and control device according to claim 1 and a mechanism for coupling said device to each individual pole of the circuit breaker.

11. (Amended) A high or medium voltage disconnector characterized in that it comprises an actuation and control device according to claim 1.

IN THE ABSTRACT

Please amend the Abstract on page 15 to read as follows:

ABSTRACT

An actuation and control device for opening and/or closing an electric switchgear which is connected to an electrical network and has at least one fixed contact and at least one movable contact. The actuation and control device includes an actuator operatively connected to the movable contact to supply the energy to perform opening/closing operations. A measuring mechanism detects the voltage and/or the current of at least one of

the phases of the network. The actuator includes a motor with position control, which is operatively connected to the movable contact, and an electronic control and power supply unit which receives information from the measuring mechanism and, following an operation command, sends to the motor electrical signals for driving the motor so that the movement of the movable contact is controlled in relation to a predetermined operation time and to the received information.

REMARKS


Favorable consideration of this application, as presently amended, is respectfully requested.

The present Preliminary Amendment is submitted to place the above-identified application in more proper format under United States practice. By the present Preliminary Amendment the claims have been amended to no longer recite any improper multiple dependencies. The Abstract has also been amended to delete legal phraseology and to be in more proper format under United States practice.

The present application is believed to be in condition for a full and thorough examination on the merits. An early and favorable consideration of the present application is hereby respectfully requested.

Respectfully submitted,

OBLON, SPIVAK, McCLELLAND,
MAIER & NEUSTADT, P.C.



Gregory J. Maier
Attorney of Record
Registration No. 25,599
Surinder Sachar
Registration No. 34,423



22850

Tel.: (703) 413-3000
Fax: (703) 413-2220
GJM:SNS\la
I:\atty\SNS\217867us-pr.wpd

217867US-2X PCT

Marked-Up Copy
Serial No: _____
Amendment Filed on: _____
1-14-2002

IN THE CLAIMS

Please amend the claims as follows:

--3. (Amended) An actuation and control device according to [one or more of the previous claims] claim 1, characterized in that position control is performed by a position sensor on the motor.

4. (Amended) An actuation and control device according to [one or more of the previous claims] claim 1, characterized in that said motor with position control is a rotary servomotor.

5. (Amended) An actuation and control device according to [one or more of the previous claims] claim 1, characterized by the fact that said electronic control and power supply unit comprises:

- calculating means suitable for predicting the zeros and maximums of the voltage and of the current of the phases subsequent to those detected by said measuring means and for calculating the period of time between the zeros and maximums detected and those predicted.

8. (Amended) A pole of a high-voltage circuit breaker, characterized in that it comprises an actuation and control device according to [one or more of claims 1 to 7] claim 1.

9. (Amended) A three-pole high-voltage circuit breaker for opening and closing a circuit connected thereto, characterized in that it comprises, for each pole, an actuation and control device according to [one or more of claims 1 to 7] claim 1.

10. (Amended) A three-pole high-voltage circuit breaker for opening and closing a circuit connected thereto, characterized in that it comprises an actuation and control device according to [one or more of claims 1 to 7] claim 1 and a mechanism for coupling said device to each individual pole of the circuit breaker.

11. (Amended) A high or medium voltage disconnector characterized in that it comprises an actuation and control device according to [one or more of claims 1 to 7] claim 1.--

IN THE ABSTRACT

Please amend the Abstract page 15 to read as follows:

--[ACTUATION AND CONTROL DEVICE FOR ELECTRIC SWITCHGEAR]

ABSTRACT

An actuation and control device for opening and/or closing an electric switchgear which is connected to an electrical network and has at least one fixed contact and at least one movable contact[, comprising actuation means which are]. The actuation and control device includes an actuator operatively connected to the movable contact [and] to supply the energy to perform opening/closing operations[, and]. A measuring mechanism detects [means for detecting] the voltage and/or the current of at least one of the phases of [said] the network[, the actuation means comprising]. The actuator includes a motor with position control, which is operatively connected to the movable contact, and an electronic control and power supply unit which receives information from the measuring [means] mechanism and, following an

operation command, sends to the motor electrical signals for driving the motor so that the movement of the movable contact is controlled in relation to a predetermined operation time and to the received information.--

10/030684

ACTUATION AND CONTROL DEVICE FOR ELECTRIC SWITCHGEARDESCRIPTION

The present invention relates to an actuation and control device for opening/closing an electric switchgear, for example circuit breakers, disconnectors and the like, particularly for high- and medium-voltage transmission and/or distribution networks, i.e. for voltages higher than 1000 Volt.

In particular, the actuation and control device according to the present invention allows to improve maneuvers of the switchgear from both a mechanical and an electrical point of view, making it possible to perform the electrical operations in a "synchronous" and repeatable manner in relation to the network parameters. The device according to the present invention is particularly adapted for use in high-voltage circuit breakers and is now described with reference to this application without limiting in any way its scope of application.

As it is known, a single pole of a high voltage circuit breaker comprises a first post-shaped supporting insulator arranged on a supporting frame, a second insulator which is arranged on the upper end of said first insulator, and an interruption chamber, with interruption mechanisms constituted by fixed contacts and movable contacts, which is provided inside said second insulator. The movable contacts are operatively connected to an actuation rod, which runs inside the first insulator from the movable contacts to the base of the post. The rod is actuated by means of kinematic systems located in a housing at the base of the post and operatively connected to an actuation device.

Closing and opening of the circuit breaker are performed in relation to a control signal sent, for example, by a control panel or by a protection logic; in particular, this signal is sent to the actuation device that causes engaging and disengaging of the fixed contacts from the movable contacts.

At the present state of the art, currently used actuation devices, generally of the mechanical or hydraulic type, are structurally complicated and operate according to a not adjustable rule of motion. For example, mechanical actuation devices generally use two springs, namely a closure spring and an opening spring, a stroke-limiting shock absorber, a reloading motor for the closure spring, and a mechanism which allows to convert the motion produced by the springs into a translatory motion of the movable contact, reload the opening spring, and make the opening movement independent of the closure movement. Besides the very large number of components which require long and complicated initial adjustment, one severe drawback resides in the fact that the movement of the movable contact is determined exclusively by the elastic characteristic of the opening and closure springs; the rule of motion of the movable contact cannot be changed by the user but is set during design. Actuation devices of the hydraulic type, in which the movement of the movable contact is ensured by adapted hydraulic actuators, can partially obviate these drawbacks, but have disadvantages linked to the presence of fluids, particularly owing to their temperature-sensitivity.

As a matter of fact, opening or closing operations of the circuit breakers are generally asynchronous in relation to the phases of the electrical parameters, which is to say they do not have any temporal relationship with the electrical network; this in most cases leads to the generation of transients in the electrical network due to prestrike phenomena during closing and restrike phenomena during opening. In particular, depending on the type of load present in the electrical network, an operation performed at a non-optimal moment could cause high frequency oscillation phenomena with high amplitudes compared to the rated values of the electrical parameters of the electrical network; the current values can, for example, even rise several orders of magnitude higher than the rated current value. These transients clearly subject the electrical

network to anomalous stresses and have the potential to cause malfunctioning of the electronic protections, to reduce the expected life of the equipment connected to the electrical network and even to lead to the shutdown of said equipment with high detriment to the continuity of power supply, especially in industrial plants. Moreover they lead in any case to a greater wear of the contacts of the circuit breaker itself and consequently reduce its useful life.

The absence of control over the rule of motion of the actuation device also requires the presence of dampers or shock- absorbers to dissipate the residual kinetic energy at the end of the actuation and to avoid uncontrolled impacts against the pole. Furthermore, precision in the positioning of the movable contact is limited by a mechanism, which is inherently inaccurate owing to the presence of the springs.

Owing to the large number of components, the devices of the prior art require maintenance in order to maintain their nominal behavior and thus ensure repeatability of the actuation by compensating for variations due to system wear and aging. Actuation repeatability in any case has inherent limits.

Moreover, the energy that must be supplied is higher than the energy strictly required to move the movable contact, since it is necessary to also move the various mechanical elements of the switchgear.

The aim of the present invention is to provide an actuation and control device for an electric switchgear, such as for example circuit breakers, disconnectors, and the like, which allows to control the actuation of the switchgear in such a way to perform opening or closing operations synchronously, taking as a reference at least one individual phase, in relation to the electrical parameters of the network, irrespective of the command instant sent from a control panel or a protection logic. It should be understood that the opening and/or closing operation may be considered synchronous when, having set an ideal tripping moment in relation to the type of load and the load and network neutral

connection to ground, such as for example the zero voltage for a capacitor or the peak voltage for a reactive load, the disengagement/engagement of the contacts falls within a synchronization time window around the ideal moment, so that the transients obtained are sufficiently low.

5 Within the scope of this aim, an object of the present invention is to provide an actuation and control device for an electric switchgear, such as for example circuit breakers, disconnectors and the like, which enables to obtain synchronism of the operation with the waveform of the electrical network with different types of networks and loads present, thus distinguishing itself by
10 considerable flexibility in use.

Another object of the present invention is to provide an actuation and control device for an electric switchgear, such as for example circuit breakers, disconnectors and the like, that guarantees the repeatability of the operation to be performed as well as its optimization in relation to the different types of
15 breaking techniques chosen.

A further object of the present invention is to provide an actuation and control device for an electric switchgear, such as for example circuit breakers, disconnectors and the like, that allowing to obtain operations that are synchronous with the waveform of the electrical network makes it possible to
20 increase its reliability while also increasing the electrical and mechanical life of equipment present in it.

Another object of the present invention is to provide an actuation and control device for an electric switchgear, such as for example circuit breakers, disconnectors and the like, which has reduced mechanical complexity.

25 A further object of the present invention is to provide an actuation and control device for an electric switchgear, such as for example circuit breakers, disconnectors and the like, that makes it possible to decrease the energy used in

the operation, thus making it possible to optimize the sizing of the actuator and of the power supply system, with a consequent economic benefit.

Not the last object of the present invention is to provide an actuation and control device for an electric switchgear, such as for example circuit breakers, disconnectors and the like, that is highly reliable and relatively easy to manufacture at competitive costs.

Thus the present invention relates to an actuation and control device for opening and/or closing an electric switchgear which is connected to an electrical network and has at least one fixed contact and at least one movable contact, comprising actuation means which are operatively connected to the movable contact and supply the energy to perform opening/closing operations, measuring means for detecting the voltage and/or the current of at least one of the phases of said network. The device according to the invention is characterized in that said actuation means comprise a motor with position control, which is operatively connected to the movable contact, and an electronic control and power supply unit which receives information from said measuring means and, following an operation command, sends to the motor electrical signals for driving said motor so that the movement of the movable contact is controlled in relation to a predetermined operation time and to said received information.

The actuation and control device thus conceived allows to accurately control the actuation of the switchgear and makes it possible to realize opening/closing operations which are synchronized, taking as a reference at least one of the phases of the electrical network. In this way, the voltage and current transients of the electrical network are eliminated, or at least limited as much as possible, thus reducing any anomalous stresses on the equipment presents. Furthermore, by using a motor with position control, the actuation and control device is also considerably simplified with respect to switchgear of the prior art, since it allows to eliminate the springs, the motor for reloading the closure spring, and all the

mechanisms that allow to perform the switching cycles; accordingly, bulk is also reduced, and repeatability of maneuvers is guaranteed.

Further characteristics and advantages of the invention will become apparent from the description of some preferred but not exclusive embodiments of an actuation and control device for opening and/or closing an electric switchgear, illustrated only by way of non-limitative example in the accompanying drawings, wherein:

figure 1 is a block diagram of a device according to the invention;

figure 2 is a block diagram showing schematically an electronic control and power supply unit used in the device according to the invention;

figure 3 is a view of a pole of a high-voltage circuit breaker provided with a device according to the invention;

figure 4 is a view of a three-pole circuit breaker provided with a single actuation and control device according to the invention;

Figure 5 is a diagram illustrating the voltage phase in relation to time in normal operating conditions;

Figure 6 is a diagram illustrating the current phase in relation to time in the presence of a transient.

With reference to figure 1, the actuation and control device according to the invention comprises an electronic control and power supply unit 100, which following an operation command 1 (arriving for example from an operator or from a protection system) actuates a motor with position control 2. The motor 2 is operatively connected to the movable contact 3 of an electric switchgear 4 by means of an adapted kinematic chain 5. In its turn, the switchgear 4, which comprises also at least one fixed contact 8, is connected to an electrical network 30; measuring means 31, for example current or voltage transformers, are provided for detecting the voltage and/or the current of at least one of the phases of said network 30.

Position control is generally performed by means of a position sensor located on the motor 2, which sends to the control unit 100 information 7 related to the movement of said motor 2. Position control can also be performed by a position sensor for the movable contact, which sends to the control unit 100 information
5 related to the actual position of the movable contact 3. Said position sensor can simply be a limit switch, which reports to the control unit 100 that the required switching action has been completed.

Preferably, the motor 2 with position control is constituted by a rotary servomotor with a position sensor. In this case, the connection between the
10 motor and the movable contact occurs by means of a kinematic pair, which is capable of converting the rotary motion of the driving shaft into a translatory motion of the movable contact. The use of a servomotor allows high power levels to be available with very short delivery times. For an equal power, it is furthermore possible to act with two independent control parameters (torque
15 and/or speed), allowing greater flexibility during design.

The electronic control and power supply unit 100 is generally powered directly by the network 30. However, the device preferably also has an auxiliary energy-accumulation power supply system 101. Preferably, said system, constituted for example by a battery of capacitors, must be able to store and
20 deliver at least the energy required for a quick opening/closing/opening (OCO) switching cycle.

As it will be described in detail hereinafter, by means of the control and power supply unit 100 it is possible to drive the motor 2 so that the movement of the movable contact 3 can be controlled in a simple and flexible manner, as a
25 function of the operating command received, of a predetermined operation time, and of the type of fault possibly detected, and to perform opening/closing operations which are synchronized with respect to the current and/or the voltage of at least one of the phases of the network 30.

In particular, as illustrated in Figure 2, in a preferred embodiment of the device according to the invention, the electronic control and power supply unit 100 comprises calculating means 11 which receive by said measuring means 31 information 32 tracking the electrical parameters of the network; in relation to this information, the calculating means 11, through suitable calculations, predict the succession of the zeros and maximums of the current and/or voltage of the phases following those detected, also taking account of frequency variations, harmonic components and single-phase transient components. In addition, they calculate the time between the zeros and maximums detected and those predicted, and send an indicative signal 38 to a timer and command unit 36.

In addition, the electronic control and power supply unit 100 advantageously comprise table means 34 that contain predetermined information regarding the type of load, the electrical network, the load and neutral network connection to ground, and send a signal 35 indicating the ideal end-of-operation times in relation to said predetermined information to a timer and command unit 36; furthermore, if it is required by the applications, said table means contain also information about the state of the neutral of the network 30. In this embodiment and as illustrated in Figures 5 and 6, the operation command 1 is sent to the timer and command unit 36 and is a command that is generally asynchronous in relation to the electrical network. The timer and command unit 36 outputs a corresponding synchronous start operating command 37 to the motor 2; this synchronous command 37 is delayed in relation to the asynchronous command 1 by a period of time 50 that is a function of the predetermined nominal operating time 51 and of the said signals 35 and 38 indicating the ideal end-of-operation times and the subsequent zeros or maximums predicted respectively, in order to identify the first subsequent ideal moment useful for implementing the synchronous operation. The desired ideal

moment 35 is clearly the optimal time for eliminating operation transients in relation to the type of operation, load and electrical network; as illustrated in Figure 6, this moment in time does not necessarily coincide with a zero or with a maximum but nevertheless ensures that the operation is performed within the synchronism window around the optimal instant.

A significant advantage of the invention resides in the fact that, by using a motor 2 with a position control, information about the movement of the movable contact 3 is sent to the electronic control and power supply unit 100 at each instant; in this way, it is possible to execute corrective actions, if any, during the maneuver, thus performing a control in real time and ensuring execution of the operation in a predetermined nominal operation time. Moreover, position control performed on the motor (and/or on the movable contact 3) allows braking the movable contact at the end of the switching action, thus eliminating the need to use a shock absorber, and to have a great repeatability of the maneuvers as well. Recovery of energy during breaking operations is also possible, thereby reducing the total energy consumption.

If however, the deviation from the nominal behaviour at any point becomes accentuated during the operation, requiring a significant correction, the device is able to correct the predetermined nominal operation time in a self-organizing mode. In this case, the nominal operation time that is suitably monitored during the operations is redefined in relation to a new reference value; this new reference time is obviously made available to the unit 100.

It has in practice been noted how the device as in the invention makes it possible to achieve the task in full as well as the objects set in that it makes it possible to control the operations of the switchgear and to perform actuation of the movable contact 3 according to a controlled rule of motion, thus allowing to obtain operations which are synchronous with the electrical network, with

the widest different types of electrical systems and loads present in them and even in the presence of faults.

This therefore results in significant advantages in terms of the elimination, or at least significant reduction of voltage and current transients in the network, as well as in terms of limiting electrodynamic and thermal stresses, with significant consequent benefits both for equipment present in the electrical network and of the switchgear used, considerably increasing its useful life and reliability.

The device according to the invention is conveniently applied in various kinds of electric switchgear, such as circuit breakers, disconnectors and the like, and is particularly adapted for high-voltage circuit breakers. Figure 3 illustrates, schematically, an example of a pole of a high-voltage circuit breaker which comprises a control and actuation device according to the invention, indicated by the reference number 200, which is connected to the movable contact 3, not shown in figure, by means of a rod 26.

If the electrical switchgear is constituted by a three- pole high-voltage circuit breaker for opening and closing a circuit connected thereto, each individual pole can comprise an actuation and control device according to the invention. In this manner, by appropriately programming the electronic control and power supply unit 100, it is possible to provide a synchronous opening or closing action, in a very flexible way. For example, it is possible to use measuring means 31 for each phase of the electrical network 30 and to perform synchronized operation for each phase, independently from the others. Alternatively, it is possible to provide measuring means 31 for only one phase, which is considered as a reference, and to assume that the network is electrically symmetrical, namely that each phase is shifted from the previous of 120 electrical degrees.

In a further embodiment, shown in figure 4, the three-pole circuit breaker can have a single actuation and control device according to the invention; in such

situations, the device is mechanically coupled to each individual pole of the circuit breaker by adopting suitable rods 24. In this case, information on the electrical network is given by measuring means provided on a single phase.

In practice, it has been found that the actuation and control device according to
5 the invention fully achieves the intended aim, since it allows to improve the characteristics of electric switchgear by controlling the rule of motion of the movable contact.

In addition to the above advantages, the actuation and control device allows to reduce costs by reducing the parts, reducing the calibration operations and
10 eliminating movements and stresses that can give rise to impact damage. Accordingly, maintenance costs are also reduced.

The device thus conceived is susceptible of modifications and variations, all of which are within the scope of the inventive concept; all the details may furthermore be replaced with technically equivalent elements. In practice, the
15 materials used, so long as they are compatible with the specific use, as well as the dimensions, may be any according to the requirements and the state of the art.

ART 34 AMDT

CLAIMS

1. An actuation and control device for opening and/or closing an electric switchgear (4) which is connected to an electrical network (30) and has at least one fixed contact (8) and at least one movable contact (3), comprising
5 actuation means which are operatively connected to the movable contact (3) and supply the energy to perform opening/closing operations, and measuring means (31) for detecting the voltage and/or the current of at least one of the phases of said network (30), characterized in that said actuation means
10 comprise a motor with position control (2), which is operatively connected to the movable contact (3), and an electronic control and power supply unit (100) which receives information from said measuring means (31) and, following an operation command (1), sends to the motor (2) electrical signals for driving said motor (2) so that the movement of the movable contact (3) is controlled in relation to a predetermined operation time and to said received
15 information.
2. An actuation and control device according to claim 1 characterized in that the opening and/or closing is synchronized with respect to at least one of the phases of the electrical network (30).
3. An actuation and control device according to one or more of the previous
20 claims, characterized in that position control is performed by a position sensor on the motor (2).
4. An actuation and control device according to one or more of the previous claims, characterized in that said motor with position control (2) is a rotary servomotor.
- 25 5. An actuation and control device according to one or more of the previous claims, characterized by the fact that said electronic control and power supply unit (100) comprises:
 - calculating means (11) suitable for predicting the zeros and maximums of the voltage and of the current of the phases subsequent to those detected by

said measuring means (31) and for calculating the period of time between the zeros and maximums detected and those predicted.

6. An actuation and control device according to claim 5 characterised by the fact that said electronic control and power supply unit (100) comprises table means (34) containing predetermined information regarding the type of load and the load and network neutral connection to ground, said table means (34) being able to output a signal (35) indicating the ideal end-of-operation times in relation to said predetermined information.

7. An actuation and control device according to claim 6 characterized by the fact that said electronic control and power supply unit (100) comprises a timer and command unit (36) that receives in input:

- an operation command (1) that is asynchronous in relation to the electrical network (30);

- the signal indicating the ideal end-of-operation times (35);

- the signal indicating the subsequent predicted zeros or maximums (38);

and outputs a corresponding synchronous operating command (37) that is delayed in relation to said asynchronous operating command (1) by a period of time (50) that is a function of the predetermined operation time (51) and of said signals (35, 38) indicating the ideal end-of-operation times and the predicted subsequent zeros or maximums.

8. A pole of a high-voltage circuit breaker, characterized in that it comprises an actuation and control device (200) according to one or more of claims 1 to 7.

9. A three-pole high-voltage circuit breaker for opening and closing a circuit connected thereto, characterized in that it comprises, for each pole, an actuation and control device (200) according to one or more of claims 1 to 7.

10. A three-pole high-voltage circuit breaker for opening and closing a circuit connected thereto, characterized in that it comprises an actuation and control device (200) according to one or more of claims 1 to 7 and a mechanism (24) for coupling said device (200) to each individual pole of the circuit breaker.

14-05-2001

EP 112-PCT

10030684..052002

EP 000005941

ART 34 AMDT

11. A high or medium voltage disconnecter characterized in that it comprises an actuation and control device (200) according to one or more of claims 1 to 7.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
25 January 2001 (25.01.2001)

PCT

(10) International Publication Number
WO 01/06528 A1(51) International Patent Classification⁷: **H01H 11/00**(74) Agent: **GIAVARINI, Francesco**; ABB Ricerca S.p.A.,
Viale Edison, 50, I-20099 Sesto San Giovanni (IT).(21) International Application Number: **PCT/EP00/05941**(22) International Filing Date: **20 June 2000 (20.06.2000)**(25) Filing Language: **English**(26) Publication Language: **English**(30) Priority Data:
99202306.9 **14 July 1999 (14.07.1999) EP**(71) Applicant (for all designated States except US): **ABB RE-
SEARCH LTD [CH/CH]**; Affolternstrasse 44, P.O. Box
8131, CH-8050 Zurich (CH).

(72) Inventors: and

(75) Inventors/Applicants (for US only): **ELLI, Enrico**
[IT/IT]; Via Leopardi, 4, I-20050 Verano Brianza (IT).
GEMME, Carlo [IT/IT]; Via Fratelli Coda, 11/5, I-16166
Genova Quinto (IT). **TESTI, Giandomenico** [IT/IT];
Corso Vittorio Veneto, 17, I-24046 Osio Sotto (IT).(81) Designated States (national): **AU, BA, BG, BR, CA, CN,
CU, CZ, EE, HR, HU, ID, IL, IN, JP, KE, KP, KR, LT, LV,
MK, MX, NO, NZ, PL, RO, SG, SI, SK, TR, UA, US, YU.**(84) Designated States (regional): **ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), OAPI
patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR,
NE, SN, TD, TG).****Published:**


- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **ACTUATION AND CONTROL DEVICE FOR ELECTRIC SWITCHGEAR**

(57) Abstract: An actuation and control device for opening and/or closing an electric switchgear which is connected to an electrical network and has at least one fixed contact and at least one movable contact, comprising actuation means which are operatively connected to the movable contact and supply the energy to perform opening/closing operations, and measuring means for detecting the voltage and/or the current of at least one of the phases of said network, the actuation means comprising a motor with position control, which is operatively connected to the movable contact, and an electronic control and power supply unit which receives information from the measuring means and, following an operation command, sends to the motor electrical signals for driving the motor so that the movement of the movable contact is controlled in relation to a predetermined operation time and to the received information.

WO 01/06528 A1






Fig. 2




Fig. 3






Fig. 4





Declaration and Power of Attorney for Patent Application

Dichiarazione e procura ai fini della domanda di brevetto

Italian Language Declaration

Il sottoscritto inventore dichiara che:

La propria residenza, recapito postale e cittadinanza corrispondono a quanto indicato in calce, sotto la propria firma.

Ritiene di essere il primo ed unico inventore originale (se viene elencato in calce un solo nominativo) o il coinventore primo ed originale (se è elencato più di un nominativo) del oggetto rivendicato e per il quale il sottoscritto presenta domanda di brevetto. La invenzione in questione è chiamata.

Actuation and control device for

electric switchgear

e la sua descrizione è allegata alla presente Dichiarazione a meno:

☐ è qui allegato

☒ Il 20 June 2000 ✓

è stata depositata una domanda di brevetto statunitense numero o una domanda di brevetto internazionale PCT numero

PCT/EP00/05941 ✓ che è stata modificata il

_____ (se applicabile).

Il sottoscritto dichiara in oltre di aver letto e compreso il contenuto della descrizione identificata in precedenza, rivendicazioni comprese, come modificati dall'eventuale modifica summenzionata.

Il sottoscritto riconosce l'obbligo di rivelare informazioni essenziali ai fini della determinazione della brevettabilità ai sensi del Titolo 37, Codice dei Regolamenti Federali, § 1.56.

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

the specification of which:

☐ is attached hereto.

☐ was filed on _____

as United States Application Number or PCT International Application Number

_____ and was amended on

_____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

Italian Language Declaration

Il sottoscritto rivendica con la presente la priorità prevista dal Titolo 35, Codice degli Stati Uniti, § 119(e)(d) o § 365(b) in relazione a qualsiasi domanda o domande estere di brevetto o certificato di inventore, o dal Titolo 35, § 365(a) degli stessi Codice in relazione a qualsiasi domanda internazionale PCT nella quale è designato almeno un paese diverso dagli Stati Uniti, i suddetti domande e certificati essendo elencati sotto, e, spuntando los seguenti caselle, ha anche identificato sotto qualsiasi domanda estera di brevetto o certificato di inventore, o domanda internazionale PCT, la cui data di deposito preceda quella dalla domanda per la quale è rivendicata la priorità.

Prior Foreign Application(s)
(Domande Estere Anteriori)

99202306_9 Europe
(Number) (Country)
(Numero) (Nazione)

(Number) (Country)
(Numero) (Nazione)

Il sottoscritto rivendica con la presente i benefici previsti dal Titolo 35, Codici degli Stati Uniti, § 119(e), in relazione a qualsiasi domanda o domande provvisorie degli Stati Uniti elencate sotto.

(Application No.)
(N° della domanda)

(Filing Date)
(Data di deposito)

Il sottoscritto rivendica con la presente i benefici previsti dal Titolo 35, Codice degli Stati Uniti, § 120, in relazione a qualsiasi domanda o domande statunitensi, o dal Titolo 35, § 365(c) degli stessi Codice in relazione a qualsiasi domanda internazionale PCT nella quale sono designati gli Stati Uniti, i suddette domande essendo elencate sotto e, nella misura in cui l'oggetto di ciascuna rivendicazione di questa domanda non sia stato esposto nella domanda statunitense o internazionale PCT anteriore nel modo previsto dal primo paragrafo del Titolo 35, Codice degli Stati Uniti, § 112, riconosce l'obbligo di rivelare informazioni essenziali ai fini della determinazione della brevettabilità ai sensi del Titolo 37, Codici dei Regolamenti Federali, § 1.56, le quali diventino disponibili durante il periodo compreso tra la data di deposito della domanda anteriore e la data di deposito nazionale o internazionale PCT della presente domanda.

(Application No.)
(N° della domanda)

(Filing Date)
(Data di deposito)

(Application No.)
(N° della domanda)

(Filing Date)
(Data di deposito)

Con la presente, il sottoscritto dichiara veritiere tutte le affermazioni contenute in questa domanda in relazione alle proprie conoscenze e di ritenere vere tutte le affermazioni o informazioni presentate. Dichiara inoltre che tali asserzioni sono state espresse nella piena consapevolezza che le dichiarazioni intenzionalmente false sono punibili con una poutte, l'incarcerazione o entrambe, ai sensi della Sezione 1001 del Titolo 18 del Codice degli Stati Uniti e che tali dichiarazioni intenzionalmente false possono mettere a repentaglio la validità della domanda o di qualsiasi brevetto rilasciato in merito.

I hereby claim foreign priority under Title 35, United States Code, § 119(a) (d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below, and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority claimed
Diritto di priorità
rivendicato

14/07/1999 ✓
(Day/Month/Year Filed)
(Giorno/Mese/Anno di deposito)

☒ Yes
SI ☐ No
No

(Day/Month/Year Filed)
(Giorno/Mese/Anno di deposito)

☐ Yes
SI ☐ No
No

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

(Application No.)
(N° della domanda)

(Filing Date)
(Data di deposito)

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Status) (patented, pending, abandoned)
(Stato) (concessione di brevetto, in corso di esame, abbandono)

(Status) (patented, pending, abandoned)
(Stato) (concessione di brevetto, in corso di esame, abbandono)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Italian Language Declaration

PROCURA: Il sottoscritto inventore nomina con la presente il seguente avvocato o avvocati e/o agente o agenti al fine di istruire questa pratica e di condurre tutte le operazioni ad essa pertinenti presso l'Ufficio dei Brevetti e Marchi di Fabbrica (Elencare il nome ed il numero di matricola).

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: (list name and registration number)



022850

Inviare le corrispondenza a:

Send Correspondence to:



022850

Telefonare a:
(Nome e numero telefonico)

Direct Telephone calls to: (name and telephone number)

(703) 413-3000

Nome e cognome dell'unico o del primo inventore		Full name of sole or first inventor	
1-00 Enrico ELLI	Date	Inventor's signature	Date
Firma dell'inventore	February 04, 2002		
Residenza		Residence	
Verano in Brianza (MI) I.TX			
Cittadinanza		Citizenship	
Italian			
Recapito postale		Post Office Address	
Via Leopardi, 4			
I 20050 Verano in Brianza (MI) Italy			
Nome e cognome dell'eventuale secondo coinventore		Full name of second joint inventor, if any	
2-00 Carlo GEMME	Date	Second inventor's signature	Date
Firma del secondo coinventore	February 04, 2002		
Residenza		Residence	
Genova Quinto, I.TX			
Cittadinanza		Citizenship	
Italian			
Recapito postale		Post Office Address	
Via Fratelli Coda, 11/5			
I 16166 Genova Quinto Italy			

(Fornire le stesse informazioni e le firme del terzo e degli ulteriori coinventori.)

(Supply similar information and signature for third and subsequent joint inventors)

Italian Language Declaration

Nome per intero di un eventuale terzo co-inventore <u>Giandomenico TESTI</u>		Full name of third joint inventor, if any	
Firma del Terzo Inventore <i>Giandomenico Testi</i>	Data <u>04.02.2002</u>	Third inventor's signature	Date
Residenza <u>Osio Sotto (BG) ITX</u>		Residence	
Cittadinanza <u>Italian</u>		Citizenship	
Recapito postale <u>Corso Vittorio Veneto, 17</u>		Post Office Address	
I 24046 Osio Sotto (BG) Italy			
Nome per intero di eventuale quarto co-inventore		Full name of fourth joint inventor, if any	
Firma Quarto Inventore	Data	Fourth inventor's signature	Date
Residenza		Residence	
Cittadinanza		Citizenship	
Recapito postale		Post Office Address	
Nome per intero di un eventuale quinto co-inventore		Full name of fifth joint inventor, if any	
Firma Quinto Inventore	Data	Fifth inventor's signature	Date
Residenza		Residence	
Cittadinanza		Citizenship	
Recapito postale		Post Office Address	
Nome per intero di un eventuale sesto co-inventore		Full name of sixth joint inventor, if any	
Firma del Sesto Inventore	Data	Sixth inventor's signature	Date
Residenza		Residence	
Cittadinanza		Citizenship	
Recapito postale		Post Office Address	

(Si prega di fornire simili informazioni e firme per il terzo e gli eventuali ulteriori co-inventori.)

(Supply similar information and signature for third and subsequent joint inventors.)